

**Description**

STABROM 909 biocide is a single-feed, liquid stabilized bromine biocide for industrial water treatment applications. Product halogen activity is approximately 15% as Br<sub>2</sub>, equivalent to approximately 7% as Cl<sub>2</sub>.

The active biocide ingredients are bromosulfamate and chlorosulfamate salts at approximately 18%.

**Applications**

STABROM 909 biocide is EPA-registered for use as a fungicide, algicide, slimicidal and microbiocide in recirculating cooling and process water systems, heat transfer systems (such as hydrostatic sterilizers and retorts, pasteurizers and warmers, and batch and continuous cookers), air washers and industrial scrubbing systems, containerized ponds and decorative fountains, industrial once-through cooling water systems, pulp and paper mills, wastewater systems.

It is also EPA-registered to control biofilm deposits from pumps, pipework, heat exchangers and filters associated with industrial water treatment systems.

Please contact Albemarle Corporation if you have any questions regarding STABROM 909 biocide applications.

**Specifications**

Total halogen as Br<sub>2</sub>, wt% .....14.5 – 15.9  
 Appearance .....clear yellow to clear orange liquid  
 pH .....12.4 - 14.0  
 Specific gravity @ 20° C/20° C.....1.295 - 1.370

**Typical Properties**

Density, lb/gal @ 77 °F .....10.8 - 11.4  
 Density, g/mL @ 25 °C .....1.29 - 1.37  
 Boiling point, °F (°C), approx. ....223 (106)  
 Freezing point, °F (°C), approx. ....32 (0)  
 Viscosity, cSt @ 77 °F (25 °C) .....2  
 Vapor pressure, mm Hg @ 77 °F (25 °C) .....19  
 Solubility in water ..... complete  
 Odor .....mild, sweet

**Storage Information**

STABROM 909 biocide should be stored away from incompatible materials. To maximize product shelf life, the product should be stored in a cool, dry, well-ventilated area in opaque containers, to minimize exposure to light and especially sunlight. As the product ages, activity is gradually lost and nitrogen pressure can build up in the headspace, therefore, the product should be stored in vented containers.

Avoid freezing, excessive heat or exposure to light, especially direct sunlight. Heating of the product above what is needed for freeze protection should be avoided as it can accelerate decomposition. Temperature monitoring is recommended. Precautions should be taken to ensure that the average temperature of the product is maintained below 110 °F.

This product retains 95% of its initial activity for at least one year when properly stored at ambient temperatures (<80 °F), and protected from light.

## Compatibility

### Compatible

STABROM 909 biocide, at its end-use concentration, is compatible with commonly used materials of construction in cooling systems. In its neat form, at ambient temperatures, this product is compatible with titanium, Hastelloy® C-276, Monel 400, vinyl tubing, high-density polyethylene, polypropylene, PVC, Viton®, Teflon®, Tygon® tubing, chlorobutyl rubber, Hypalon®, HALAR® ECTFE, Tefzel® ETFE, W.L. Gore GORE-TEX® GR, W.L. Gore UPG Style 800, and Garlock Gylon® Styles 3504, 3500, and 3510.

### Incompatible

In its neat form, this product is not compatible with Buna-N rubber, neoprene, silicone rubber, Plasite® 4300 and 3070, nylon, aluminum, brass, carbon steel, copper, stainless steel and other common metals. This product is strongly basic and an oxidizing agent. Contact with organic materials such as alcohols and aldehydes, strong reducing agents, strong oxidizers, acids, and ammonia-containing products should be avoided. Use of incompatible materials can promote the exothermic decomposition of the product. In extreme cases, this could result in vigorous gas formation and over-pressurization of storage containers.

---

## Shipping Information

### Container Information

Available in bulk, totes and drums

### Shipping Classification

Proper shipping name: CORROSIVE LIQUIDS, BASIC, INORGANIC, N.O.S.  
(Halogenated Complex, Sodium Hydroxide)

Hazard class: 8

ID number: UN3266

Label/placard: corrosive w/number 8

Packing group: III

---

## Safety and Handling Information

For specific safety, handling and toxicity information please refer to the current material safety data sheet.

---

## Regulatory Information

Use of this product is regulated by the U.S. EPA and enforced by state agencies. It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

U.S. EPA registration number: 3377-55

---

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.



**NORTH AMERICA** 451 Florida Street • Baton Rouge, Louisiana 70801-1765 • Tel: 225.388.7402 or 800.535.3030 • Fax: 225.388.7848

**LATIN AMERICA** 451 Florida Street • Baton Rouge, Louisiana 70801-1765 • Tel: 1.225.388.7908 • Fax: 225.388.7848

**EUROPE** Parc Scientifique de LLN • Rue du Bosquet 9 • B-1348 Louvain-la-Neuve Sud, Belgium • Tel: 32.10.48.1711 • Fax: 32.10.48.1717

**MIDDLE EAST** Bldg. 6W Block-A Office #512 • Dubai Airport Free Zone (DAFZA) • Dubai • United Arab Emirates • Tel: 971.4.701.7770 • Fax: 971.4.701.7780

**ASIA PACIFIC** Room 2208, Shui On Plaza • No. 333 Huai Hai Zhong Road • Shanghai 200021 China • Tel: 86.21.6103.8666 • Fax: 86.21.6103.8777

**ASIA PACIFIC (Japan Only)** 16th Floor, Fukoku Seimei Building • 2-2-2, Uchisaiwai-cho • Chiyoda-ku, Tokyo 100-0011, Japan • Tel: 81.3.5251.0796 • Fax: 81.3.3500.5623

**ASIA PACIFIC** #602 Trade Tower, World Trade Center • 159-1 Samsung-dong Kangnam-gu • Seoul 135-729 Korea • Tel: 82.2.555.3005 • Fax: 82.2.555.3002

**ASIA PACIFIC** 490 Lorong 6 Toa Payoh #09-10 • HDB Hub Biz 3 • Singapore 310490 • Tel: 65.6.424.8400 • Fax: 65.6.424.8400