

## TECHNICAL DATA SHEET

Date of Issue: 2025/11/28

# Lithium Hydride, powder < 100 µm

CAS-No.	7580-67-8
EC-No.	231-484-3
REACH No.	01-2119918290-45-0000
Molecular formula	LiH
Product number	10000103

---

<b>APPLICATION</b>	Reducing agent, high density hydrogen source, production of high purity monosilanes.
--------------------	--

---

### SPECIFICATION

---

LiH	min. 97 %
Na	max. 0.9 %
K	max. 0.05 %

---

### PHYSICAL PROPERTIES

Appearance	powder
Colour	white to grey
Melting point/ range	688 °C
Density	0.78 g/cm <sup>3</sup> at 20 °C
Bulk density	290 - 400 kg/m <sup>3</sup>

---

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website [www.albemarle.com](http://www.albemarle.com).

Please contact us at [www.albemarle.com/contact](http://www.albemarle.com/contact) with questions.



Product number: 10000103

Date of Issue: 2025/11/28

Water solubility (Substance hydrolyses rapidly.)

Molecular weight 7.95 g/mol

Thermal Stability Decomposition: abt. 800 °C

Additional Physical Properties Theoretical hydrogen content: 12.7 %, equivalent to 2.82 litres of hydrogen per g evolved in hydrolysis Heat of fusion: approx. 2.5 kJ/g H<sub>2</sub> equilibrium pressure: 500 °C: 0.09 mbar 850 °C: approx. 1,010 mbar

## HANDLING & STORAGE

**Handling** Lithium Hydride should be handled under inert gas atmosphere. Avoid contact with eyes, skin and clothes as well as inhalation. In use may form flammable/explosive dust-air mixtures. Lithium Hydride decomposes in contact with humidity. Pay also attention to the Safety Data Sheet.

**Storage** Lithium Hydride should be stored in tightly closed containers under exclusion of humidity at gentle temperatures. Keep away from heat, sparks and fire. When stored according to SDS and under exclusion of air and humidity, the material is fairly stable. We still recommend to retest the material 6 months after date of analysis if included on CoA. If not included, use the date of manufacturing for the calculation. Pay also attention to the Safety Data Sheet

## TRANSPORT & PACKAGING

UN number 1414

ADR	Class: 4.3	PG: I	Label: 4.3
RID	Class: 4.3	PG: I	Label: 4.3
IMDG	Class: 4.3	PG: I	Label: 4.3
IATA_C	Class: 4.3	PG: I	Packing instruction (cargo aircraft): 487
IATA_P	Class: 4.3	PG: I	

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Hazard pictograms



Signal word

Danger

H&P Phrases

See Safety Data Sheet

Labelling

The labelling is according to EU-GHS classification ((EG) 1272/2008) and may vary in other countries. Please refer to the respective Safety Data Sheet for your country.

Packaging

Inner Packing: Solvent soluble SecuBags® from 500 g to 2,000 g in cans and 5 kg SecuBags®. Outer

Packing: Appropriate clamping ring steel drums.

---

**OTHER INFORMATION**

Further Related Documents

Safety Data Sheet

Our brochure(s)

Metal Hydrides

---

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.