

TECHNICAL DATA SHEET

Date of Issue: 2021/07/22

Calcium Hydride, Grade O

CAS-No.	7789-78-8
EC-No.	232-189-2
REACH No.	01-2120774384-47-0000
Molecular formula	CaH ₂
Product number	10002019

APPLICATION

Calcium hydride is used primarily as a source of hydrogen, as a drying agent for liquids and gases, and as a reducing agent for metal oxides.

SPECIFICATION

Ca total	min. 92 %
H	min. 980 ml/g CaH ₂
Mg	max. 0.8 %
N	max. 0.2 %
Al	max. 0.01 %
Cl	max. 0.5 %
Fe	max. 0.01 %

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website

www.albemarle-lithium.com. Please contact us at www.albemarle-lithium.com/contact with questions.



METHOD OF ANALYSIS

Calcium complexometric, impurities by spectral analysis and special analytical procedures. Gas volumetric determination of hydrogen. Produces with water approx. 1,010 ml hydrogen per gram.

PHYSICAL PROPERTIES

Appearance	powder
Colour	white to grey
Decomposition temperature	>= 600 °C Method: OECD Test Guideline 102
Boiling point/boiling range	(Decomposes below the boiling point.)
Density	1.90 g/cm ³ at 20 °C Method: OPPTS 830.7300
Water solubility	(Substance hydrolyses rapidly.)
Molecular weight	42.1 g/mol
Grain Size	approx. 10 - 100 mm, contains up to 10 % fines

HANDLING & STORAGE

Handling	Flammable solid. Contact with water liberates highly flammable gases! Calcium hydride decomposes partially and reversibly at temperatures above 600 °C. Calcium hydride is insoluble in most organic solvents. Upon direct contact with water Calcium hydroxide [Ca(OH) ₂] and pure hydrogen gas are produced in a violent reaction and self-ignition is possible. One kg of CaH ₂ liberates approx. 1 m ³ of hydrogen. Avoid contact with water and with skin. Wear protective goggles and gloves and avoid formation of dust. In case of fire cover with dry sand, calcined soda or quicklime. Never use water, carbon dioxide, or halocarbon extinguisher. Should be handled with minimal exposure to humid air.
Storage	Store in airtight containers away from open flame.

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

TRANSPORT & PACKAGING

UN number 1404

ADR	Class: 4.3	PG: I	Label: 4.3
RID	Class: 4.3	PG: I	Label: 4.3
IMDG	Class: 4.3	PG: I	Label: 4.3
IATA_C	Class: 4.3	PG: I	Packing instruction (cargo aircraft): 487
IATA_P	Class: 4.3	PG: I	

Hazard pictograms



Signal word

Danger

H&P Phrases

See Safety Data Sheet

Labelling

The labelling is according to EU-GHS classification ((EG) 1272/2008) and may vary in other countries. Please refer to the respective Safety Data Sheet for your country.

Packaging

GGVE, GGVS, RID, ADR, IMDG: HDPE-bottle wide neck, max. 5 kg ICAO: HDPE-bottle wide neck, max. 1 kg

OTHER INFORMATION

Further Related Documents

Safety Data Sheet

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website

www.albemarle-lithium.com. Please contact us at www.albemarle-lithium.com/contact with questions.

Remarks More Information about the Application Area of Calcium Hydride

Hydrogen Generation

Calcium hydride serves as a convenient source of clean, though wet, hydrogen, by reaction with water in simple, low cost, lightweight generators. One pound of calcium hydride yields 17 cubic feet of hydrogen at S.T.P. By reaction with water, calcium hydride generates twice the amount of hydrogen as expected from its empirical formula according to the following reaction: $\text{CaH}_2 + 2\text{H}_2\text{O} \rightarrow \text{Ca(OH)}_2 + 2\text{H}_2$

This property is most useful in energy storage applications.

Drying Agent

Calcium hydride dries gases and liquids by irreversible reaction with water according to the equation shown above. By this reaction, 7 kg of CaH_2 will remove 6 kg of water. Please keep in mind: 7 kg of CaH_2 generate approx. 7 m3 of hydrogen when mixed with two equivalents of water.

Typical Industrial Drying with Calcium Hydride

Phase	Method	Contact Temp. (Time)	Water (ppm)
Hydrogen			
Gas	Fixed Bed	60 °C (for 1 min.)	initial 100 ppm - final 1 ppm
Argon			
Gas	Fixed Bed	30 °C (for 1 min.)	initial 5000 ppm - final 1 ppm
Hydrocarbon			
Gas	Fixed Bed	30 °C (for 0.2 min.)	initial 40 ppm - final 1 ppm
Liquid	Fixed Bed	30 °C (for 30 min.)	initial 200 ppm - final 1 ppm
Ether			
Liquid	Stirred Tank	30 °C (for 240 min.)	initial 400 ppm - final 1 ppm

Because of potentially dangerous reactions, CaH_2 is not recommended for drying chlorinated or fluorinated carbon compounds.

Reducing Agent

At high temperatures, CaH_2 reduces refractory oxides to the metals.

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.