

TECHNICAL DATA SHEET

Date of Issue: 2021/07/22

Cesium Sulfate, purity min. 99.9 %

CAS-No.	10294-54-9
EC-No.	233-662-6
REACH No.	01-2119977125-33-0000
Molecular formula	Cs ₂ SO ₄
Product number	10001873, 10001874, 10001875

APPLICATION	This product is used for density gradient centrifugation and as a promoter in catalytic systems.
--------------------	--

PURITY	min. 99.9 %
---------------	-------------

SPECIFICATION

Li	max. 5 ppm
Na	max. 150 ppm
K	max. 300 ppm
Rb	max. 100 ppm
Ca	max. 10 ppm
Mg	max. 10 ppm
Sr	max. 10 ppm
Ba	max. 10 ppm

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website

www.albemarle-lithium.com. Please contact us at www.albemarle-lithium.com/contact with questions.



Al	max. 5 ppm
Fe	max. 5 ppm
Cr	max. 5 ppm
Mn	max. 5 ppm
Cl	max. 100 ppm

Deliveries are accompanied by a lot specific certificate of analysis. If any of these values is critical to your application, please let us know.

PHYSICAL PROPERTIES

Appearance	Crystalline powder
Colour	colourless to white
Melting point/range	1,006 °C at 1,013 hPa Method: OECD Test Guideline 102
Flash point	(Not applicable)
Density	4.25 g/cm ³ at 20 °C Method: OECD Test Guideline 109
Bulk density	2,000 - 2,500 kg/m ³
Water solubility	> 1,000 g/l at 20 °C Method: OECD Test Guideline 105
Molecular weight	361.87 g/mol

HANDLING & STORAGE

Handling	Handling in moist air should be avoided.
Storage	Because of its hygroscopicity cesium sulfate should be stored in tightly closed containers.

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

TRANSPORT & PACKAGING

ADR

Not regulated as a dangerous good

Hazard pictograms



Signal word

Warning

H&P Phrases

See Safety Data Sheet

Labelling

The labelling is according to EU-GHS classification ((EG) 1272/2008) and may vary in other countries. Please refer to the respective Safety Data Sheet for your country.

Packaging

Polyethylene bottles or bags with aluminium barrier in drums (fiber drums, clamping ring drums, steel drums, steel drums with polypropylene inner lining). The aluminium barrier prevents diffusion of moisture into the product. Alternative packaging on request. Smaller units available at surcharge.

OTHER INFORMATION

Further Related Documents

Safety Data Sheet

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website

www.albemarle-lithium.com. Please contact us at www.albemarle-lithium.com/contact with questions.