

TECHNICAL DATA SHEET

Date of Issue: 2021/07/22

Titanium Hydride, Grade G

| | |
|-------------------|-----------------------|
| CAS-No. | 7704-98-5 |
| EC-No. | 231-726-8 |
| REACH No. | 01-2120760622-57-0000 |
| Molecular formula | TiH ₂ |
| Product number | 10002007 |

APPLICATION

Titanium hydride powders find application in both pyrotechnic and metallurgical areas. They are utilized in initiator squibs and igniters. They are also used as getters in the manufacture of vacuum tubes, as brazing aids in sealing ceramics to metals, the introduction of titanium to alloys; as reservoir for pure hydrogen; as hydrogen source for foaming metals; as a deoxidizing agent and for the absorption of carbon in powder metallurgy; for the production of Ti alloys and semi-finished sintered articles; as a constituent in AlNiCo and TiCoNiAl sintered magnets; used for increasing the coercivity of FeNiCoAlCu magnets.

SPECIFICATION

| | |
|-------------------|-------------|
| Particle Size D50 | 50-70µm |
| H | min. 3.8 % |
| Ti | ≥ 95 % |
| Fe | max. 0.09 % |

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website

www.albemarle-lithium.com. Please contact us at www.albemarle-lithium.com/contact with questions.



METHOD OF ANALYSIS

Determination of particle size distribution, combustion properties and gain on ignition. Gravimetric analysis of titanium and determination of hydrogen and Fe.

PHYSICAL PROPERTIES

| | |
|---------------------|--|
| Appearance | powder |
| Colour | grey to black |
| Melting point/range | > 400 °C (Decomposes before melting.) |
| Density | 3.91 g/cm ³ at 20 °C Method: OPPTS 830.7300 |
| Bulk density | 2,500 kg/m ³ |
| Water solubility | < 0.001 g/l at 22 °C (practically insoluble) |
| Molecular weight | 49.9 g/mol |

HANDLING & STORAGE

Handling Highly flammable solid. Dust explosion hazard. Stable titanium hydride powder of high purity, yielding hydrogen at elevated temperatures in a reversible reaction; easily pressed and sintered. Like Ti metal, TiH₂ is resistant to most chemical reagents, but is attacked at elevated temperature by oxidizing agents and acids. TiH₂ is attacked by cold hydro fluoric acid solutions. Safe to handle at room temperature. At elevated temperatures and low pressures the generation of hydrogen must be considered. Risk of dust explosion. In case of fire cover with dry sand or dry chemical/dolomite (powdered limestone). Never extinguish with water, carbon dioxide, or halocarbon. See our safety data sheet and special precautionary advice for more information on safety.

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

TRANSPORT & PACKAGING

UN number 1871

| | | | |
|--------|------------|--------|---|
| ADR | Class: 4.1 | PG: II | Label: 4.1 |
| RID | Class: 4.1 | PG: II | Label: 4.1 |
| IMDG | Class: 4.1 | PG: II | Label: 4.1 |
| IATA_C | Class: 4.1 | PG: II | Packing instruction (cargo aircraft): 448 |
| IATA_P | Class: 4.1 | PG: II | Packing instruction (passenger aircraft): 445 |

Hazard pictograms



Signal word

Danger

H&P Phrases

See Safety Data Sheet

Labelling

The labelling is according to EU-GHS classification ((EG) 1272/2008) and may vary in other countries. Please refer to the respective Safety Data Sheet for your country.

Packaging

Titanium hydride is packed in polyethylene bags overpacked in tin cans of 2.5 kg and 15 kg TiH₂ capacity. Other packaging sizes on request.

OTHER INFORMATION

Further Related Documents

Safety Data Sheet

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website

www.albemarle-lithium.com. Please contact us at www.albemarle-lithium.com/contact with questions.