

# TECHNICAL DATA SHEET

Date of Issue: 2017/11/09

## n-Pentyllithium, typ. 25 % solution in Heptane (typ. 2.2 M)

{ error: file not found:  
D:\WWI\graphics\401755.jpg  
g }

CAS-No. 3525-31-3

EC-No. not registered

Molecular Formula  $C_5H_{11}Li$

Product Number 401755

---

**APPLICATION** Alkylating agent

---

### FURTHER INGREDIENTS

Heptane

CAS-No. 64742-49-0

EC-No. 927-510-4

---

### SPECIFICATION

n-Pentyllithium: 23 - 27 %

---

### METHOD OF ANALYSIS

Determination of assay as total base; detailed description available on request.

---

### PHYSICAL PROPERTIES

Appearance liquid

Color colourless to yellow clear

---

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website [www.albemarle-lithium.com](http://www.albemarle-lithium.com). Please contact us at [www.albemarle-lithium.com/contact](http://www.albemarle-lithium.com/contact) with questions.



Crystallization temperature	-10 °C
Flash point	< 0 °C (Heptane)
Boiling point/boiling range	83 - 105 °C (Heptane)
Density	ca. 0.70 g/cm <sup>3</sup> at 25 °C
Water solubility	(Not applicable)
Molecular weight	78.08 g/mol
Thermal Stability	Decomposition above 35 °C

---

## HANDLING & STORAGE

Handling	Handling only under inert gas (nitrogen or argon). Product is spontaneously flammable in air. Pay attention to official safety regulations (see also: "Transport regulations" and "GHS Hazard Pictograms").
Storage	Under exclusion of air humidity the solution is stable. Recommended storage temperature: -10 to 35 °C. Keep container tightly closed. Keep away from sources of ignition. Take precautionary measures against static discharges.

---

## TRANSPORT & PACKAGING

UN number 3394

ADR	Class: 4.2	PG: I	Label: 4.2 (4.3)
RID	Class: 4.2	PG: I	Label: 4.2 (4.3)
IMDG	Class: 4.2	PG: I	Label: 4.2 (4.3)
IATA_C	Class: 4.2		
IATA_P	Class: 4.2		

---

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website [www.albemarle-lithium.com](http://www.albemarle-lithium.com). Please contact us at [www.albemarle-lithium.com/contact](http://www.albemarle-lithium.com/contact) with questions.

Hazard pictograms



Signal Word

Danger

H&P Phrases

See Safety Data Sheet

Labelling

The labelling is according to EU-GHS classification ((EG) 1272/2008) and may vary in other countries. Please refer to the respective Safety Data Sheet for your country.

Packaging

Glass bottles of 100, 250, 500 and 1,000 ml. Steel bottles and containers with nominal volumes of 7.4, 27, 127 and 450 l. For safety reasons these are filled to a maximum of 90 %.

---

OTHER INFORMATION

Further Related Documents

Safety Data Sheet

Our brochure(s)

Organomagnesium Compounds

---

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website [www.albemarle-lithium.com](http://www.albemarle-lithium.com). Please contact us at [www.albemarle-lithium.com/contact](http://www.albemarle-lithium.com/contact) with questions.