


# TECHNICAL DATA SHEET

Date of Issue: 2018/03/07

## Sodium tert-Amoxide, typ. 40 % solution in Toluene, OH stabilized (typ. 3.3 M)



CAS-No.	14593-46-5
EC-No.	238-639-4
REACH No.	01-2119919041-51
Molecular Formula	C <sub>5</sub> H <sub>11</sub> NaO
Product Number	408123

---

APPLICATION	Deprotonation reactions in organic syntheses.
-------------	---

---

### FURTHER INGREDIENTS

Toluene	
CAS-No.	108-88-3
EC-No.	203-625-9
Sodium Hydroxide	
CAS-No.	1310-73-2
EC-No.	215-185-5
EC-No.	2151855

---

### SPECIFICATION

---

Sodium tert-Amoxide	39 - 41 %
NaOH + Na <sub>2</sub> CO <sub>3</sub>	0.4 - 1.1 % *)

---

\*) calculated as NaOH

---

### METHOD OF ANALYSIS

Acidimetric titration of the hydrolyzed product for the determination of total base. Detailed description available on request. Determination of NaOH by Karl Fischer titration.

---

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website [www.albemarle-lithium.com](http://www.albemarle-lithium.com). Please contact us at [www.albemarle-lithium.com/contact](http://www.albemarle-lithium.com/contact) with questions.

 **ALBEMARLE®**

Product Number: 408123

Date of Issue: 2018/03/07

---

## PHYSICAL PROPERTIES

Color	yellowish to brownish
Crystallization temperature	< 10 °C
Flash point	4 °C (Information taken from reference works and the literature.)
Boiling point/boiling range	ca. 110 - 111 °C (Toluene)
Density	0.91 g/cm <sup>3</sup> at 20 °C
Water solubility	(Not applicable)
Molecular weight	110.13 g/mol

---

## HANDLING & STORAGE

Handling	Sodium tert-Amoxide should be handled under inert gas atmosphere. Avoid contact with eyes, skin and clothes as well as inhalation.  Sodium tert-Amoxide decomposes in contact with humidity.  Pay also attention to the Safety Data Sheet.
Storage	Sodium tert-Amoxide should be stored in tightly closed containers under exclusion of humidity at gentle temperatures. The product starts to form crystalline precipitates on cooling below abt. 10 °C. Recommended storage temperature: min. 15 °C. Keep away from heat, sparks and fire. Pay also attention to the Safety Data Sheet.

---

## TRANSPORT & PACKAGING

UN number 2924

ADR	Class: 3	PG: II	Label: 3 (8)
RID	Class: 3	PG: II	Label: 3 (8)
IMDG	Class: 3	PG: II	Label: 3 (8)
IATA_C	Class: 3	PG: II	Packing instruction (cargo aircraft): 363
IATA_P	Class: 3	PG: II	Packing instruction (passenger aircraft): 352

---

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website [www.albemarle-lithium.com](http://www.albemarle-lithium.com). Please contact us at [www.albemarle-lithium.com/contact](http://www.albemarle-lithium.com/contact) with questions.

Product Number: 408123

Date of Issue: 2018/03/07

---

Hazard pictograms



Signal Word                      Danger

H&P Phrases                      See Safety Data Sheet

Labelling                      The labelling is according to EU-GHS classification ((EG) 1272/2008) and may vary in other countries. Please refer to the respective Safety Data Sheet for your country.

Packaging

Glass bottles of 100, 250, 500 and 1,000 ml. Steel bottles with volumes of 7.4, 27, 127 or 450 l. For safety reasons these are filled to a maximum of 90 %. Steel drums up to 200 l.

---

OTHER INFORMATION

Further Related                      Safety Data Sheet  
Documents

Our brochure(s)                      Alkoxides, Trifold - Specialties for Deprotonation

---

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website [www.albemarle-lithium.com](http://www.albemarle-lithium.com). Please contact us at [www.albemarle-lithium.com/contact](http://www.albemarle-lithium.com/contact) with questions.