

TECHNICAL DATA SHEET

Date of Issue: 2016/12/13

Lithium Diisopropylamide, typ. 25 % solution in Heptane / THF / Ethylbenzene (typ. 1.9 M)

{ error: file not found:
D:\WWI\graphics\408413.jp
g }

CAS-No.	4111-54-0
EC-No.	223-893-0
REACH No.	01-2119917565-33
Molecular Formula	C ₆ H ₁₄ LiN
Product Number	408413

APPLICATION Strong, low-nucleophilic base for e.g. enolisations.

FURTHER INGREDIENTS

Heptane

CAS-No.	64742-49-0
EC-No.	927-510-4

Tetrahydrofuran

CAS-No.	109-99-9
EC-No.	203-726-8

Ethylbenzene

CAS-No.	100-41-4
EC-No.	202-849-4

Diisopropylamine

CAS-No.	108-18-9
EC-No.	203-558-5

SPECIFICATION

LDA (active base)	24 – 26 % (1.9 M)
THF	17 – 27 %
technical Heptane	31 – 39 %
Ethylbenzene	11 – 15 %

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website www.albemarle-lithium.com. Please contact us at www.albemarle-lithium.com/contact with questions.



Product Number: 408413

Date of Issue: 2016/12/13

Diisopropylamine	max. 4 %
------------------	----------

METHOD OF ANALYSIS

Direct titration with benzoic acid against 4-phenyl-azo-diphenyl-amine for the determination of active base (modified Watson-Eastham). Detailed description available on request.

PHYSICAL PROPERTIES

Appearance	liquid
Color	slightly yellow to red brown
Crystallization temperature	< 0 °C
Decomposition temperature	> 40 °C
Flash point	-21.2 °C (Tetrahydrofuran)
Boiling point/boiling range	66 °C (Tetrahydrofuran)
Density	ca. 0.80 g/cm ³ at 20 °C
Water solubility	(Not applicable)
Molecular weight	107.13 g/mol

HANDLING & STORAGE

Handling	Lithium Diisopropylamide should be handled under inert gas atmosphere. Avoid contact with eyes, skin and clothes as well as inhalation. Lithium Diisopropylamide decomposes in contact with humidity. Pay also attention to the Safety Data Sheet.
----------	--

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website www.albemarle-lithium.com. Please contact us at www.albemarle-lithium.com/contact with questions.

Product Number: 408413

Date of Issue: 2016/12/13

Storage Lithium Diisopropylamide should be stored in tightly closed containers under exclusion of humidity at gentle temperatures. The product tends to crystallize at temperatures below 0 °C. On prolonged storage at higher temperatures product is decomposing. Average decomposition rate:

at 23 °C < 0.1 wt.% (of 25 %) per day

at 40 °C < 0.3 wt.% (of 25 %) per day

Recommended storage temperature: 0 - 15 °C.

Keep away from heat, sparks and fire. Pay also attention to the Material Safety Data Sheet.

TRANSPORT & PACKAGING

UN number 2924

ADR	Class: 3	PG: II	Label: 3 (8)
RID	Class: 3	PG: II	Label: 3 (8)
IMDG	Class: 3	PG: II	Label: 3 (8)
IATA_C	Class: 3	PG: II	Packing instruction (cargo aircraft): 363
IATA_P	Class: 3	PG: II	Packing instruction (passenger aircraft): 352

Hazard pictograms



Signal Word Danger

H&P Phrases See Safety Data Sheet

Labelling The labelling is according to EU-GHS classification ((EG) 1272/2008) and may vary in other countries. Please refer to the respective Safety Data Sheet for your country.

Packaging

Glass bottles of 100, 250, 500 and 1,000 ml. Steel bottles with volumes of 7.4, 27, 127 or 450 l. For safety reasons these are filled to a maximum of 90 %. Steel drums up to 200 l net.

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website www.albemarle-lithium.com. Please contact us at www.albemarle-lithium.com/contact with questions.

OTHER INFORMATION

Further Related Documents

Safety Data Sheet

Our brochure(s)

Lithium & Magnesium Amides, Trifold - Specialties for Deprotonation

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website www.albemarle-lithium.com. Please contact us at www.albemarle-lithium.com/contact with questions.