

# TECHNICAL DATA SHEET

Date of Issue: 2017/09/06

## Ethylmagnesium Bromide, typ. 40 % solution in Diethyl Ether (typ. 3.1 M)



CAS-No.	925-90-6
EC-No.	213-127-3
REACH No.	01-2120065578-44
Molecular Formula	C <sub>2</sub> H <sub>5</sub> MgBr
Product Number	408475

---

**APPLICATION** Grignard-reactions: reagent for the introduction of the ethyl group.

---

### FURTHER INGREDIENTS

Diethyl ether

CAS-No.	60-29-7
EC-No.	200-467-2

---

### SPECIFICATION

Ethylmagnesium Bromide: 39.0 – 41.0 %

---

### METHOD OF ANALYSIS

Determination of assay as total base by acidimetric titration after hydrolysis; detailed description available on request.

---

### PHYSICAL PROPERTIES

Appearance	liquid
Color	dark brown

---

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website [www.albemarle-lithium.com](http://www.albemarle-lithium.com). Please contact us at [www.albemarle-lithium.com/contact](http://www.albemarle-lithium.com/contact) with questions.

Product Number: 408475

Date of Issue: 2017/09/06

Crystallization temperature	ca. -10 °C
Flash point	-45 °C (Diethyl ether)
Boiling point/boiling range	ca. 34.7 °C at 1,013 hPa (Diethyl ether)
Density	1.03 g/cm <sup>3</sup> at 20 °C
Water solubility	(Hydrolyzes on contact with water.)
Molecular weight	133.27 g/mol
Thermal Stability	crystallisation below around -10 °C

## HANDLING & STORAGE

Handling	Organomagnesium compounds should only be handled under inert gas (nitrogen or argon). Never add water, acids or oxidizing materials to the product. In case of fire use dry extinguishers on basis of sodium chloride or limestone powder. Never use water or CO <sub>2</sub> -extinguishers. Pay attention to official safety regulations (see also: "Transport regulations" and "GHS Hazard Pictograms").
Storage	Under exclusion of air and humidity stable over practically unlimited periods. Keep container dry and tightly closed.

## TRANSPORT & PACKAGING

UN number 3399

ADR	Class: 4.3	PG: I	Label: 4.3 (3)
RID	Class: 4.3	PG: I	Label: 4.3 (3)
IMDG	Class: 4.3	PG: I	Label: 4.3 (3)
IATA_C	Class: 4.3	PG: I	Packing instruction (cargo aircraft): 494
IATA_P	Class: 4.3	PG: I	

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website [www.albemarle-lithium.com](http://www.albemarle-lithium.com). Please contact us at [www.albemarle-lithium.com/contact](http://www.albemarle-lithium.com/contact) with questions.

Hazard pictograms



Signal Word

Danger

H&P Phrases

See Safety Data Sheet

Labelling

The labelling is according to EU-GHS classification ((EG) 1272/2008) and may vary in other countries. Please refer to the respective Safety Data Sheet for your country.

Packaging

Glass bottles of 100, 250, 500 and 1,000 ml. Steel bottles with volumes of 7.4, 27, 127 or 450 l. For safety reasons these are filled to a maximum of 90 %. Steel drums up to 200 l.

---

OTHER INFORMATION

Further Related Documents

Safety Data Sheet

Our brochure(s)

Organolithium Compounds

---

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website [www.albemarle-lithium.com](http://www.albemarle-lithium.com). Please contact us at [www.albemarle-lithium.com/contact](http://www.albemarle-lithium.com/contact) with questions.