

TECHNICAL DATA SHEET

Date of Issue: 2019/03/07

Lithium Fluoride, technical grade

CAS-No.	7789-24-4
EC-No.	232-152-0
REACH No.	01-2120751214-63
Molecular Formula	FLi
Product Number	401281

APPLICATION

Fluxes for welding and soldering techniques; salt bath for heat-treatment by low temperature and for dip brazing; fluxing agent for the glass, ceramics and enamel industries; additive in aluminum-electrolysis melts; raw material for optical lenses and prisms.

SPECIFICATION

LiF	min. 98.0 %
LOD (110 °C)	max. 0.50 %
Fe ₂ O ₃	max. 0.15 %
Sulfur	max. 0.05 %
CO ₂ as Li ₂ CO ₃	max. 1.0 %
Heavy Metals as Pb	max. 0.01 %

PHYSICAL PROPERTIES

Appearance	crystalline
Color	colorless
Melting point/ range	848 °C at 1,013 hPa (Information taken from reference works and the literature.)
Flash point	(Not applicable)
Boiling point/boiling range	1,681 °C at 1,013 hPa (Information taken from reference works and the literature.)
Density	2.64 g/cm ³ at 20 °C (Information taken from reference works and the literature.)

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website www.albemarle-lithium.com. Please contact us at www.albemarle-lithium.com/contact with questions.



Bulk density ca. 400 kg/m³Water solubility 1.3 g/L at 25 °C (Information taken from reference works and the literature.)

HANDLING & STORAGE

Handling No special precautions necessary but inhalation as well as contact with skin have to be avoided. Pay attention to official safety regulations (see also: "Transport regulations" and "GHS Hazard Pictograms").

TRANSPORT & PACKAGING

ADR

Not regulated as a dangerous good

Hazard pictograms



Signal Word Warning

H&P Phrases See Safety Data Sheet

Labelling The labelling is according to EU-GHS classification ((EG) 1272/2008) and may vary in other countries. Please refer to the respective Safety Data Sheet for your country.

Packaging

100 lbs polyethylene bags in clamping ring drums

OTHER INFORMATION

Further Related Documents Safety Data Sheet

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

Technical data sheets may change frequently. You can download the latest version from our website www.albemarle-lithium.com. Please contact us at www.albemarle-lithium.com/contact with questions.